

VLCD-7 (V2)

2 CH 7" LCD Monitor

The VLCD-7 (V2) is a 2 CH LCD monitor for safety and security. With a rugged, commercial grade design and removable sunshield, the VLCD-7 (V2) provides clear and vivid video resolution ideal for any type of vehicle.

- 7" TFT / LCD Screen
- 2 CH Video Input (RCA)
- 800 x 480 Resolution
- 9V 16V DC Input
- Rugged, Commercial Grade
- Normal, Mirror, Vertical Flip View Option
- OSD Control Brightness, Contrast, Sharpness, Saturation
- Removable Sunshield
- Remote Control Included



BENEFITS OF VENTRA MONITORS

- Reduce Blind Spots
- Easily Identify Person / Object / Distance
- Reduce Damage and Injury

- Improve Overall Safety
- Enhance Productivity
- Convenience and Peace of Mind

VLCD-7 (V2)

Any type of Industry











VLCD-4

2 CH 4" LCD Monitor

The VLCD-4 is a 2 CH high quality video resolution monitor for safety, and security. With a rugged, commercial grade design, the VLCD-4 provides clear and vivid video resolution ideal for any type of vehicle.

- 4.3" TFT / LCD Screen
- 2 CH Video Input (RCA)
- 480 x 272 Resolution
- 9V 32V DC Input
- High Quality Video Resolution
- OSD Control Brightness, Contrast, Sharpness, Saturation
 Built-in Sunshield



CAMERA AND KIT ACCESORIES

BACK UP CAMERA RVC-1B



ACCESORIES / CAMERA EX4-XC2



ACCESORIES / CAMERA EX4-XC4

The VICD 4 feetures h

FEATURES

The VLCD-4 features big power with a small footprint. It has a compact design best suitable for confined spaces.

- Rideshare App Security
- PA Transportation
- Delivery Services

MONITOR	VLCD-4
Screen Size	4.3" TFT LCD
Video Input	2 Channels
Video Connection	RCA x 2
Resolution	480 x 272 Pixel
Sunshade	Fixed
Color Configuration	RGB
Speaker / Audio	N/A
View Mode	N/A
OSD Control	Brightness, Contrast, Sharpness, Tint
Environment Rating	Interior
TV System	NTSC / PAL
Camera Power	DC 9V ~ 16V
Humidity	<90%
Temperature Range (Operating)	-4F ~ 150F (-20C ~ + 65C)
Dimension Without Bracket	120 (W) x 26 (D) x 187 (H) mm

MONITOR	VLCD-7 (V2)
Screen Size	7" TFT LCD
Video Input	2 Channels
Video Connection	RCA x 2
Resolution	800 x 480 Pixel
Sunshade	Removable
Color Configuration	RGB
Speaker / Audio	N/A
View Mode	Normal, Mirror, Vertical Flip
OSD Control	Brightness, Contrast, Sharpness, Saturation
Environment Rating	Interior
TV System	NTSC / PAL
Camera Power	DC 9V ~ 32V 160mA
Humidity	<90%
Temperature Range (Operating)	-4F ~ 150F (-20C ~ + 65C)
Dimension Without Bracket	172 (W) x 21 (D) x 113 (H) mm